

NOTES:

- 1. 6 FOOT AND 10 FOOT CHAIN LINK FENCE SHALL CONFORM TO THE CITY STANDARD DETAIL SD-19.
- 2. PLAYERS BENCH SHALL CONFORM TO THE PARK STANDARD DETAIL PSD SPORT-7.
- 3. INFIELD EDGE BAND AT BACK STOP AND FOUL LINE FENCE SHALL CONFORM TO THE PARK STANDARD DETAIL PSD SPORT-10.
- 4. RAMP SHALL BE REQUIRED IF THERE IS A CHANGE IN ELEVATION BETWEEN ADJACENT SURFACING AND PROPOSED FIELD SURFACE. RAMP INTO DUGOUT SHALL BE A MINIMUM OF 1% AND A MAXIMUM OF 4.9%. GRADE BREAK SHALL EXIST AT TOP AND BOTTOM OF RAMP
- 5. DUGOUT ENTRY TO FIELD SURFACE TO BE 5'-0" CLR AT CORNER POST WITH CLEAR SPACE IN DUGOUT
- 6. CONCRETE SURFACE SHALL ALWAYS HAVE A CROSS SLOPE OF 1.8% WITH A TOLERANCE OF ±0.2%.
- 7. THICKENED EDGE IS REQUIRED TO ACCOMMODATE DIFFERENCE IN ELEVATION OF ADJACENT SURFACING. IF A DIFFERENCE IN ELEVATION DOES NOT EXIST, ELIMINATE THICKENED EDGE AND POUR CONCRETE DUGOUT SURFACE FLUSH WITH ADJACENT SURFACE.
- PLAYER BENCH SHALL BE 25' IN LENGTH, ALUMINUM PEDESTAL LEG BENCH, EMBEDDED FOOTING.
- 9. INSTALL BENCH AND FOOTING PER MANUFACTURER'S SPECIFICATIONS AND RECOMMENDATIONS.

0 2' 4' 8' 12'

SCALE: 3/32" = 1'-0"

			CIT	Y OF	FREMO	ONT	DATE APPROVED BY CITY COU December 13, 2011	NCIL
			PARK STANDARD DETAILS				RESOLUTION NO. 2011-65	
							SENIOR LANDSCAPE ARCHITECT	
			DUGOUT LAYOUT				REParent fact	
APR.	RE∨ISED	DATE					COMMUNITY SERVICES DIRECTOR	
	REVISION	IS					annelle Hole	
FILE NO.		SCALE		DRAWN	CHECKED	DATE	DWG NO.	
PSD SPORT-8.DWG		3/32" = 1'-0"		MAM	RER	03/14/2011	PSD SPORT-8	1 OF 1